




Dual-band Panel	824~960
Dual Polarization	X
Half-power Beam Width	65°
Fixed Electrical Downtilt	3°


XPoI 824~960MHz 65° 18dBi 3° Tilt

Electrical specifications	KBT65DP18-0809AT3	
Frequency range (MHz)	824~896	870~960
Polarization	±45°	
Gain (dBi)	2×17.5	2×18
Electrical Downtilt (°)	3	
Half-power beam width (°)	Horizontal:68 Vertical:7.5	Horizontal:65 Vertical:7
Sidelobe suppression for first sidelobe above main beam (dB)	≥15	
Front-to-back ratio (dB)	≥25	
Cross-polar discrimination (dB)	≥15(±60°≥10)	
Isolation (dB)	≥30	
Impedance (Ω)	50	
VSWR	≤1.4	
Intermodulation IM3 (2×43dBm carrier)	≤-150dBc	
Maximum power (W)	500	
Lighting protection	DC Ground	

Mechanical specifications	
Connector	2×7/16DIN Female
Connector position	Bottom
Height/width/depth (mm)	2530×280×85
Packing size (mm)	2850×380×170
Weight (kg)	20
Radome material	UPVC
Radome color	Gray
Mechanical tilt (°)	0~10
Operating temperature (°C)	-40~60
Rated wind velocity (m/s)	60
Suitable pole diameter (mm)	50~115
Mounting kit	JM-900BZ



824~896MHz: ±45° Polarization



870~960MHz: ±45° Polarization

