




Single-band Panel	1710~1880
Dual Polarization	X
Half-power Beam Width	90°
Variable Electrical Downtilt	0°-10°

XPo1 1710~1880MHz 90° 14.5dBi 0° -10° Tilt

Electrical specifications	KBT90DP15-18AE
Frequency range (MHz)	1710~1880
Polarization	±45°
Gain (dBi)	2×14.5
Electrical Downtilt (°)	0~10
Half-power beam width (°)	Horizontal:90 Vertical:11
Sidelobe suppression for first sidelobe above main beam (dB)	0°...5°...10° 16...15...13
Front-to-back ratio (dB)	≥23
Cross-polar discrimination (dB)	≥15(±60°≥10)
Isolation (dB)	≥30
Impedance (Ω)	50
VSWR	≤1.5
Intermodulation IM3 (2×43dBm carrier)	≤-150dBc
Maximum power (W)	300
Lighting protection	DC Ground



Mechanical specifications	
Connector	2×7/16DIN Female
Connector position	Bottom
Height/width/depth (mm)	890×160×80
Packing size (mm)	1250×250×170
Weight (kg)	6.8
Radome material	UPVC
Radome color	Gray
Mechanical tilt (°)	0~15
Operating temperature (°C)	-40~60
Rated wind velocity (m/s)	60
Suitable pole diameter (mm)	50~115
Mounting kit	JM-1800BZ
Electrical downtilt adjustment	Manual or by optional RCU



1710~1880MHz: ±45° Polarization

